

KILN DRIED PAVING JOINT SAND

Ready-to-use Kiln Dried Paving Joint Sand



bringing materials to *life*™

Lafarge Kiln Dried Paving Joint Sand is a ready-to-use kiln dried fine sand.



General Information

Lafarge Kiln Dried Paving Joint Sand is suitable for finishing narrow joints between patio slabs or block paving.

This product is manufactured to a third party accredited BS EN 9001 Quality Management System.

Packaging and coverage

Lafarge Paving Joint Sand is available in weatherproof and tear-resistant plastic packaging.

1 large pack bag will be sufficient for approximately 4 m² of 50mm block paving.

Use

- Ensure that the paving surface is dry
- Simply pour the sand onto the paving
- Brush sand into joints using a stiff brush or broom

Storage

Lafarge Kiln Dried Paving Joint Sand should be handled and stored with care. Unopened bags can be stored in either outdoor or indoor conditions. Open bags should be stored in dry cool conditions protected from wind.

Normal manual handling procedures (Manual Handling Operations Regulations 1992) should be followed when unloading or moving bags.

Availability

Lafarge Kiln Dried Paving Joint Sand is available throughout Great Britain from Lafarge Cement UK stockists.

Technical Support

Further information and advice on this product and the full range of Lafarge Cement products can be obtained through the contacts listed below. Alternatively, step-by-step application videos are available from us on the internet, by scanning the QR code below using your Smartphone or by downloading our iPhone app from the App Store.

Responsible Sourcing

This product has been externally assessed and awarded a 'Very Good' classification to the prestigious BES 6001, Responsible Sourcing Standard.



Health and Safety

Lafarge Kiln Dried Paving Joint Sand poses no significant hazard, but should not be used for dry blasting. However, respirable silica inhaled over a prolonged period can be hazardous to health. If there is a risk of airborne dust, suitable control measures should be employed.

Avoid contact with eyes and skin and avoid inhaling the product.

For further information, refer to the appropriate Lafarge Cement Health and Safety Information Sheet.

For further information

Technical helpline

Tel: 0845 812 6232

E-mail: info@uk.lafarge.com

Customer services

Tel: 0845 812 6300

E-mail:

customerservice@uk.lafarge.com

iPhone App

www.lafarge.co.uk/iphone



LAFARGE CEMENT UK LTD

Portland House
Bickenhill Lane

Solihull, Birmingham
B37 7BQ

Tel. 0845 812 6400

Fax 0845 812 6200

www.lafarge.co.uk

