

QUICKSET CONCRETE

Ready-to-use Quickset Concrete



bringing materials to *life*™

Lafarge Quickset Concrete is a premixed, quick-setting concrete manufactured from cement, specially selected sand and admixtures. When sprinkled with water it sets in approximately 30 minutes.



General Information

Lafarge Quickset Concrete can be used for paths, patios, slabs, paving and floors. It is premixed and ready to use, and only requires the addition of clean water.

This product is manufactured to a third party accredited BS EN 9001 Quality Management System.

Packaging and coverage

Lafarge Quickset Concrete is available in weatherproof and tear-resistant plastic packaging.

1 bag will produce approximately 0.45 m² of concrete at a thickness of 25 mm.

Working Temperature

Do not use at temperatures below 5°C or above 30°C without taking precautions to ensure that new work is protected from freezing or drying out.

Use

- Dampen the area to be repaired on concrete ensuring that there is no standing water
- The premixed concrete should be poured from the bag into the area to be concreted. The maximum recommended depth of concrete is 50mm. Concrete naturally expands and contracts with changing temperatures, therefore to avoid cracking limit the area to be concreted to no more than 2m
- Level the dry concrete using a straight edge or trowel
- Sprinkle with water using a fine rose until wet, using a maximum of 3 litres of water per m² (do not allow pools of water to form)
- Compact the concrete using a straight edge or float

- Re-wet the concrete 2 hours after the first application of water (for indoor conditions or in dry weather, a further application of water after 12 hours may be appropriate)
- Newly finished concrete should always be protected from drying out by covering with polythene sheeting or wet hessian (sacking) for a minimum of 7 days
- Clean all tools and equipment immediately after use and before the material has set
- Lafarge Quickset Concrete sets in about 30 minutes

Storage and Shelf Life

Lafarge Quickset Concrete is a cement-based material and should be handled and stored with care. Unopened bags can be stored in either outdoor or indoor conditions. Open bags should be stored in dry cool

conditions protected from wind. Information on the maximum storage period (shelf life) of the product is shown on the bag.

Normal manual handling procedures (Manual Handling Operations Regulations 1992) should be followed when unloading or moving bags.

Availability

Lafarge Quickset Concrete is available in large pack bags throughout Great Britain from Lafarge Cement UK stockists.

Technical Support

Further information and advice on this product and the full range of Lafarge Cement products can be obtained through the contacts listed below. Alternatively, step-by-step application videos are available from us on the internet, by scanning the QR code below using your Smartphone or by downloading our iPhone app from the App Store.


Responsible Sourcing

This product has been externally assessed and awarded a 'Very Good' classification to the prestigious BES 6001, Responsible Sourcing Standard.

Health and Safety

Lafarge Quickset Concrete contains cement; contact between cement and body fluids may cause irritation, dermatitis or burns. Cement is classified as an irritant under the Chemicals (Hazard Information and Packaging) Regulations.

For further information, including control of soluble hexavalent chromium, refer to the appropriate Lafarge Cement Health and Safety Information Sheet.



For further information

Technical helpline

Tel: 0845 812 6232

E-mail: info@uk.lafarge.com

Customer services

Tel: 0845 812 6300

E-mail:

customerservice@uk.lafarge.com

iPhone App

www.lafarge.co.uk/iphone

LAFARGE CEMENT UK LTD

Portland House
Bickenhill Lane
Solihull, Birmingham
B37 7BQ

Tel. 0845 812 6400

Fax 0845 812 6200

www.lafarge.co.uk

