

SLABLAYER



bringing materials to *life*™



READY TO USE

Slablayer is a cement based material containing specially selected sand and cement for use under patio paving slabs. It is easy to use and requires no mixing and gradually over a period of time develops hardness to support the slabs.

Uses

Slablayer can be used under most types of patio slabs to provide a level surface.

Description

Slablayer consists of cement and selected aggregates.



Packaging

Slablayer is packed in new weatherproof plastic packaging.

Sitework

For best results follow these instructions:

- 1) Prepare the area to the required depth. Remove turf and any other material which will interfere with the surface being flat and level.
- 2) Place Slablayer to the required depth (optimum 25mm), and rake level. Sprinkle with water using a fine rose until the Slablayer is wet through and rake level again.
- 3) Place the paving slabs ensuring they are level and flat. (If slabs are dry, dampen the underside of the slab before laying onto the slablayer).
- 4) Ensure that no cement material is on the slabs as this will result in staining.
- 5) For filling joints and alternative methods for laying slabs and where more substantial foundation is required. See the Lafarge Cement Builders' Guide for further information.



Cleaning

All equipment should be cleaned with water. Do not flush down drains.

Coverage

This will depend on the depth of material used but as a guide three 440mm x 440mm paving slabs can be laid with one bag when the Slablayer is used at 25 mm thick.

Availability

Slablayer is available from suppliers of Lafarge Cement products. Slablayer is supplied in 20 kg plastic bags.

Technical Support

Further information and advice on this product and the full range of Lafarge Cement products can be obtained through the contacts listed below. Alternatively, step-by-step application videos are available from us on the internet, by scanning the QR code below using your Smartphone or by downloading our iPhone app from the App Store.

Storage

This product may be stored in either indoor or outdoor conditions. Information on the maximum storage period can be found on the bag. Slablayer is a cement based material and should be handled and stored with care.

Conditions of Use

- Slablayer may only be used for bedding and grounding slabs.
- Slablayer may not be used for general concreting, screeds, mortar, grout & render.
- If a particular compressive strength is required, Slablayer should not be used.
- It is essential that Slablayer is prevented from drying out too rapidly. Generally, adequate curing is achieved by protecting the material from adverse weather conditions until fully hardened and thereafter allowing to dry slowly over several days.
- The final finish quality of this material will depend upon the operative having the required skills and a familiarity with the material and its application methods.
- Normal site practice to the relevant British and European Standards should always apply. Lafarge Cement UK cannot be held responsible where workmanship has not been carried out in accordance with good practice.
- Manual handling should comply with The Manual Handling Operations Regulations 1992.

Health and Safety

Contact between cement powder and body fluids (eg sweat and eye fluids) may cause irritation, dermatitis or burns. Cement is classified as an irritant under the Chemicals (Hazard Information and Packaging) Regulations.

For further information, including control of soluble hexavalent chromium, refer to the appropriate Lafarge Cement Health and Safety Information Sheets.



The information in this datasheet is accurate at the time of printing, but Lafarge Cement UK reserve the right to amend details as part of their product development programme.

Further information

Technical helpline

Tel: 0845 812 6232
info@uk.lafarge.com

Customer services

Tel: 0845 812 6300
customerservice@uk.lafarge.com

iPhone App

www.lafarge.co.uk/iphone

LAFARGE CEMENT UK LTD

Portland House
Bickenhill Lane
Solihull, Birmingham
B37 7BQ
Tel. 0845 812 6400
Fax 0845 812 6200
www.lafarge.co.uk

